

Select Series™ Tractors

X300 | X500 | X700



These are the lawn tractors we're proudest of.

**We gave our engineers
a simple charge:**

Build the best lawn tractors you can.
Do whatever it takes.

The result is The Select Series™.
The finest John Deere has to offer.

Strong, versatile and agile, they represent
everything we've learned in the business.

And we stand behind these tractors with
a solid 4-year limited warranty.

We're proud you're
considering one.



Heavy-duty robotically welded frame is the bed-
rock of these machines. So solid, it can handle
an amazing variety of heavy-duty attachments.

Backed by a solid warranty and a simple promise.

When you become a Select Series owner, you have the comfort of knowing that this is a tractor built to exacting standards and put through rigorous testing. That's why you'll find a 4-year limited warranty on every Select Series tractor, the best in the industry. And to show how much we believe in these tractors, we also added the John Deere Promise: buy any John Deere Select Series tractor. If you are not satisfied, bring it back within 30 days of purchase and we'll give you a full refund or exchange.*

Strong statements. But, with features like the following, we feel confident making them.

Select™
SERIES
PREMIUM TRACTORS

UP TO
4 YEARS 700 HOURS
LIMITED WARRANTY

Rigorous quality control audits ensure your tractor is built to the same exact tolerances as the first one off the line.



Airflow



The iTorque™ Power System is the source for easy starts and smooth operation. Air-cooling system increases torque and engine lifespan, all while directing heat away from the operator.



4-wheel drive. 4-wheel steer. Together on the X729 and X749. So innovative, no one else in the industry has it.

Whether it's The Edge™ Xtra Cutting System or the 7-Iron™, all of our mowing decks are formed from a single sheet of heavy-gauge steel for superior strength. Not cobbled together using fabricated sections or welding more steel on.

*If you are dissatisfied with your purchase, you may bring it back to your dealer for repair or another unit or your money back.

X300 Series

Get around. Everything.



Enjoy effortless steering and speed control.

The X300s deliver all this (and more) with available four-wheel steering, and easy-to-operate Twin Touch™ transmission control pedals. A combination you won't find anywhere else in the industry.

So if you need a master of efficiency, look no farther.

Mulch

Trim on both sides, eliminate bagging and enjoy all the lawn health benefits of mulching with available The Edge™ Mulch Deck.



Twin Touch System

Twin Touch™ automatic transmission lets you easily change from forward to reverse with two-pedal foot control for effortless speed and direction changes.



Four-Wheel Steer

All four wheels turn in unison in the same direction around obstacles for extra tight turns.

Rear Collection

For the cleanest looking lawns, choose either a bagger attachment or the custom-engineered X300R dedicated rear-bagging tractor. Its TurboStar Mower System is tailor-made for wet, tall grass or leaves.



X360

The newest member of the 300 Series features power-tilt steering for fingertip control. There's also a power-lift feature which makes handling heavy attachments a breeze. The X360 is the only tractor in this category to have both power tilt steering and power lift. The X360 gets its power from the responsive 22-hp, iTorque™ Power System. Twin Touch™ foot pedals make for precise control forward or reverse. And comfort comes standard with a 15-inch tall open-back seat that is cool and comfortable.

4 YEARS 300 HOURS
LIMITED WARRANTY

X500 Series

Work anywhere.

Mow slopes with more confidence.

Till a garden.

Get out of tough situations, easier.

X500s travel where you need to go, and do heavy-duty work. How? Their wide stance enhances stability on hillsides. Traction can be increased simply by pressing a pedal. Heavy-duty frames work with ground-engaging equipment like tillers. And features like the on-board deck leveling gauge assure quality results every time.

Multi-terrain. Multi-talented: The X500 Series.



Hydraulic Power Steering

Hydraulic power steering takes 4-wheel steering to another level and provides maximum maneuverability and an uncut trim radius of only 13 inches (with 54-inch deck).

Traction Assist

Traction assist pedal locks the rear transaxle, so both rear wheels work together with maximum power. It's an exceptionally effective method to negotiate muddy ground, or to climb a hill.



Wide stance

A lower center of gravity improves stability.



Heavy-duty all-purpose tires

Extra large rear tires are perfect for tilling, increasing traction, and they're easy on turf.



The Edge™ Xtra Cutting System

Solid stamped steel decks designed with superior airflow for unmatched cut quality and uniform discharge even in the most difficult mowing conditions.

4 YEARS 500 HOURS
LIMITED WARRANTY

X700 Series

Unlimited possibilities. Ultimate comfort.



Out of all the Select Series, these are the tractors that do more work, all day long, all year long.

Till a garden at the crack of dawn. Dig-in with four-wheel drive and load mulch. Re-do the front yard, the back yard. And your neighbor's yard. All in a few hours.

The X700 can do anything and everything. Every comfort and convenience is built-in. Every point is reinforced. Every option, from a rear PTO to additional hydraulics, is on the table.

It's the ultimate John Deere. Drive one. And you'll understand.

Full-time 4WD With this full-time 4-wheel-drive, it's always on, so there's no need to manually reach for a lever. And no scuffing worries: the speed of each front wheel is automatically adjusted for optimum performance even in tight turns.



Heavy-duty frame Built with the strength to handle your toughest tasks like blading, box scraping or spraying. Add an optional 3-point hitch to use a disk harrow, cultivator or plow. Or choose an optional 540-rpm rear PTO (power take off) to add the versatility of a rear tiller.

Shaft-driven transmission

Stronger, and able to transmit more power, X700 transmissions are just as rugged as the rest of the machine.



iTorque Power Systems — Start Off Right

The John Deere iTorque makes a great first impression. Electronic fuel injection in select X700 models means they'll start cleaner, faster and more efficiently.



4 YEARS 700 HOURS
LIMITED WARRANTY

4-wheel steer on the X729 improves maneuverability and trimming performance while also saving time.

Attachments

We're naturally attached to being versatile.



With features like heavy-duty transmissions and thick C-channel steel frames, we've got the power and the frame to take on serious attachments. And with a tractor like this, you'll want to do more than just mow. So take a look at the many ways you can get even more attached to your Select Series tractor.





EQUIPMENT	X300 SERIES	X500 SERIES	X700 SERIES
Two-Stage Snow Blowers			
44-in. Blower	X	X*	
47-in. Blower		X*	X
54-in. Blower			X
Blades			
44-in. Front Blade	X		
48-in. Front Blade		X	
54-in. Front Blade			X
60-in. Mid-Mount Blade			X*
Material Collection Systems			
2-bag (7-bu) Rear Bagger	X*		
2-bag (7-bu) Power Flow Rear Bagger	X*	X	X
3-bag (14-bu) Power Flow Rear Bagger		X	X
MC519 (19-bu) Power Flow Cart	X*	X	X
52-in. or 60-in. Rotary Brooms			
Front Thatchers			
	X	X	X
Rotary Tillers			
30-in. Mechanical Drive		X*	
42-in. Hydraulic Drive		X*	X
647 Rotary Tiller (48-in.)			X
Cabs and Weather Enclosures			
Weather Enclosure	X	X	X
Hard-Side Doors, ROPS			X
Soft-Side Doors, ROPS			X
CargO Mount™ Attachments			
Bucket Holder	X*	X	X
Integral Hitch			
		X	
Rear Limited Category 1 3-pt. Hitch			
			X
Sprayers			
15 U.S. Gallon Tow-Behind	X	X	X
25 U.S. Gallon Tow-Behind	X	X	X
40 U.S. Gallon Tow-Behind		X	X
25 U.S. Gallon Mounted	X*	X	X
Tow-Behind Equipment			
40-in. Thatcherator	X	X	X
36-in. Lawn Roller	X	X	X
40-in. Spiker Aerator	X	X	X
40-in. Aerator/Spreader	X	X	X
42-in. Lawn Sweeper	X	X	X
40-in. Plug Aerator	X	X	X
48-in. Plug Aerator		X	X
110-, 125-, or 175-lb. Broadcast Spreaders	X	X	X
Manure Spreader			X
125 lb. Electric Broadcast Spreader (Mounted)	X*	X	X
Utility Carts**			
7P Utility Cart	X	X	X
10P Utility Cart	X	X	X
13 Utility Cart	X	X	X
17P Utility Cart	X	X	X
18 and 21 Utility Carts			X
**The loaded weight of the utility cart not to exceed the weight of the tractor and operator.			
45 Loader			
			X*
Tractor Shovel			
	X	X	X
Category 1 3-pt. Hitch Implements			
			X
48-in. Box Scraper, Cultivator, Disk Harrow, 10 kW Generator, 40 Gallon Sprayer, Moldboard Plow			
60-in. Landscape Rake			
60-in. Rear Blade			
*Not all attachments fit on all models within Series.			

X300 Series

Specifications

	X300	X304 (4WS)	X320/X324 (4WS)	X340
Power Systems	John Deere iTorque™	John Deere iTorque™	John Deere iTorque™	John Deere iTorque™
Engine Power*	17 hp (12.7 kW)	17 hp (12.7 kW)	22 hp (16.4 kW)	25 hp (18.6 kW)
Displacement	28.8 cu. in. (472 cc)	28.8 cu. in. (472 cc)	41.2 cu. in. (675 cc)	41.2 cu. in. (675 cc)
Cooling	Air	Air	Air	Air
Cylinders	V-Twin	V-Twin	V-Twin	V-Twin
Lubrication System	Full pressure with replaceable oil filter	Full pressure with replaceable oil filter	Full pressure with replaceable oil filter	Full pressure with replaceable oil filter
Air Cleaner	Replaceable, dry type w/ foam precleaner	Replaceable, dry type w/ foam precleaner	Replaceable, dry type w/ foam precleaner	Replaceable, dry type w/ foam precleaner
Fuel System:				
Capacity	3.3 U.S. gal.	3.3 U.S. gal.	3.3 U.S. gal.	3.3 U.S. gal.
Fuel Type	Gasoline	Gasoline	Gasoline	Gasoline
Location	Rear	Rear	Rear	Rear
Fuel Filler Opening	3-in. diameter (76 mm)	3-in. diameter (76 mm)	3-in. diameter (76 mm)	3-in. diameter (76 mm)
Ignition	Electronic	Electronic	Electronic	Electronic
Electrical System	12 volts, 15 amp, regulated	12 volts, 15 amp, regulated	12 volts, 15 amp, regulated	12 volts, 15 amp, regulated
Transmission	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Forward Speed	5.5 mph (8.9 km/h)	5.5 mph (8.9 km/h)	5.8 mph (9.3 km/h)/ 5.5 mph (8.9 km/h)	5.8 mph (9.3 km/h)
Reverse Speed	4.0 mph (6.4 km/h)	4.0 mph (6.4 km/h)	3.5 mph (5.6 km/h)	3.5 mph (5.6 km/h)
Brakes	Internal wet disc	Internal wet disc	Internal wet disc	Internal wet disc
Steering	Low effort, 2-wheel steer	Low effort, 4-wheel steer	Low effort, 2-wheel steer/ Low effort, 4-wheel steer	Low effort, 2-wheel steer
Turning Radius	16 in. (406 mm)	15 in. (381 mm)	16 in. (406 mm)/ 15 in. (381 mm)	16 in. (406 mm)
Uncut Circle Radius	28 in. (711 mm) w/ 38-in. mower 28 in. (711 mm) w/ 42-in. mower 27 in. (686 mm) w/ 42-in. mulch	16 in. (406 mm) w/ 42-in. mower	21 in. (533 mm) w/ 48-in. mower/ 9 in. (229 mm) w/ 48-in. mower	18 in. (457 mm) w/ 54-in. mower
Seat	15 in. (381 mm), open back	15 in. (381 mm), open back	15 in. (381 mm), open back	15 in. (381 mm), open back
Tires:				
Front	15x6-6	15x6-6	15x6.5-8/15x6-6	15x6.5-8
Rear	20x10-8	20x10-10	22x11-10/20x10-10	22x11-10
Lift System	Foot pedal w/38-in. and 42-in. mowers Spring assisted foot pedal w/42-in. mulch	Foot pedal	Spring-assisted foot pedal	Spring-assisted foot pedal
PTO	Electric clutch	Electric clutch	Electric clutch	Electric clutch
Dimensions:				
Height (Seat Height)	43 in. (1092 mm)	43 in. (1092 mm)	43 in. (1092 mm)	43 in. (1092 mm)
Length, Overall	72 in. (1829 mm)	72 in. (1829 mm)	72 in. (1829 mm)	72 in. (1829 mm)
Min. Storage Width (Deflector Up)	44 in. (1118 mm) w/ 38- and 42-in. mowers	44 in. (1118 mm) w/ 42-in. mower	52 in. (1321 mm) w/ 48-in. mower	57.5 in. (1460 mm) w/ 54-in. mower
Wheelbase	49.4 in. (1255 mm)	49.4 in. (1255 mm)	49.4 in. (1255 mm)	49.4 in. (1255 mm)
Weight, Approx.	574 lb. (260 kg) w/ 42-in. mower	629 lb. (285 kg) w/ 42-in. mower	681 lb. (309 kg)/ 739 lb. (335 kg) / 739 lb. (335 kg) w/ 48-in. mower	704 lb. (319 kg) with 54-in. mower
Mower Options				
Cutting Width/Blades	38 in. (965 mm)/ 2 blades 42 in. (1067 mm) side/ 2 blades 42 in. (1067 mm) mulch/ 2 blades	42 in. (1067 mm)/ 2 blades	48 in. (1219 mm)/ 3 blades	54 in. (1372 mm)/ 3 blades
Limited Warranty	4 years / 300 hours	4 years / 300 hours	4 years / 300 hours	4 years / 300 hours

X500 Series

X360	X300R
John Deere iTorque™	John Deere iTorque™
22 hp (16.4 kW)	18 hp (13.4 kW)
41.2 cu. in. (675 cc)	36.8 cu. in. (603 cc)
Air	Air
V-Twin	V-Twin
Full pressure with replaceable oil filter	Full pressure with replaceable oil filter
Replaceable, dry type w/ foam precleaner	Replaceable, dry type w/ foam precleaner
3.3 U.S. gal.	2.4 U.S. gal. (9 L)
Gasoline	Gasoline
Rear	Rear
3-in. diameter (76 mm)	3-in. diameter (76 mm)
Electronic	Electronic
12 volts, 15 amp, regulated	12 volts, 15 amp, regulated
Hydrostatic	Hydrostatic
6.2 mph (10.0 km/h)	5.3 mph (8.5 km/h)
3.5 mph (5.6 km/h)	4.0 mph (6.4 km/h)
Internal wet disc	Internal wet disc
Power-Tilt, 2-wheel steer	Low effort, 2-wheel steer
22 in. (559 mm)	19 in. (483 mm)
24 in. (610 mm) w/ 48-in. mower	29 in. (740 mm)
15 in. (381 mm), open back	15 in. (381 mm), open back
15x6.5-8	15x6-6
22x11-10	20x10-8
Hydraulic	Spring-assisted foot pedal
Electric clutch	Electric clutch
43 in. (1092 mm)	43 in. (1092 mm)
72 in. (1829 mm)	99 in. (2514 mm)
52 in. (1321 mm) w/ 48-in. mower	44 in. (1118 mm) w/ 42-in. mowers
49.4 in. (1255 mm)	49.4 in. (1255 mm)
703 lb. (319 kg) w/ 48-in. mower	704 lb. (319 kg) w/ 42-in. mower
48 in. (1219 mm)/ 3 blades	42 in. (1067 mm) TurboStar, rear-discharge, rear collect
4 years / 300 hours	4 years / 300 hours

	X500/X530	X534 (4WS)/X540
Power Systems	John Deere iTorque™	John Deere iTorque™
Engine Power*	25 hp (18.6 kW)	25 hp (18.6 kW)/26 hp (19.4 kW)
Displacement	41.2 cu. in. (675 cc)	41.2 cu. in. (675 cc)
Cooling	Air	Air/Liquid
Cylinders	V-Twin	V-Twin
Fuel System Capacity	5 U.S. gal. (18.9 L)	5 U.S. gal. (18.9 L)
Fuel Type	Gasoline	Gasoline
Ignition	Electronic	Electronic
Electrical System	15 amp, regulated	15 amp, regulated
Transmission	Hydrostatic	Hydrostatic
Forward Speed	7.2 mph (11.6 km/h)	7.2 mph (11.6 km/h)
Reverse Speed	5.2 mph (8.4 km/h)	5.2 mph (8.4 km/h)
Brakes	Internal wet disc	Internal wet disc
Steering	Low effort, 2-wheel steer/ Power, 2-wheel steer	Power, 4-wheel steer/ Power, 2-wheel steer
Tilt Steering Wheel	No	Yes
Front Axle	Cast iron	Cast iron
Turning Radius	22 in. (559 mm)	27 in. (686 mm)/22 in. (559 mm)
Uncut Circle Radius	27 in. (686 mm) w/48-in. mower/ 24 in. (610 mm) w/54-in. mower	14 in. (356 mm) w/48-in. mower, 13 in. (330 mm) w/54-in. mower/ 24 in. (610 mm) w/54-in. mower
Tires	Turf/Heavy-Duty All Purpose (rear only)	Turf/Heavy-Duty All Purpose (rear only)**
Front	16x6.5-8	16x6.5-8
Rear	24x12-12	23x9.5-12/24x12-12
Seat	15 in. with access grasp and open back	16 in. with access handle and open back
Seat Adjustment	7 in., 14 positions	7 in., 14 positions
Lift System	Foot pedal w/spring assist/Power	Power
PTO	Electric clutch	Electric clutch
Dimensions:		
Height (Seat Height)	45 in. (1143 mm)	48 in. (1219 mm)
Length, Overall	75 in. (1905 mm)	79 in. (2007 mm)
Min. Storage Width (Deflector Up)	52 in. (1321 mm) w/ 48-in. mower 57.5 in. (1460 mm) w/ 54-in. mower	52 in. (1321 mm) w/ 48-in. mower 57.5 in. (1460 mm) w/ 54-in. mower
Wheelbase	51.2 in. (1300 mm)	51.2 in. (1300 mm)
Weight, Approx.	809 lb. (367 kg) w/ 48-in. mower/ 850 lb. (386 kg) w/ 54-in. mower	905 lb. (411 kg) w/ 54-in. mower/ 874 lb. (396 kg) w/ 54-in. mower
Mower Options		
Cutting Width/Blades	48 in. (1219 mm) 3 blades or 54 in. (1372 mm) 3 blades	48 in. (1219 mm) 3 blades or 54 in. (1372 mm) 3 blades
Limited Warranty	4 years / 500 hours	4 years / 500 hours

**Turf Optional

X700 Series

Specifications

	X700	X720/X720 SE/X724 (4WS)	X728 (4WD)/X728 SE
Power Systems	John Deere iTorque™	John Deere iTorque™	John Deere iTorque™
Engine Power*	23 hp (17.2 kW)	27 hp (20.1 kW)	27 hp (20.1 kW)
Displacement	45.5 cu. in. (745 cc)	45.5 cu. in. (745 cc)	45.5 cu. in. (745 cc)
Cooling	Liquid	Liquid	Liquid
Cylinders	V-Twin	V-Twin	V-Twin
Fuel System:			
Capacity	6.5 U.S. gal. (24.6 L)	6.5 U.S. gal. (24.6 L)	6.5 U.S. gal. (24.6 L)
Fuel Type	Gasoline	Gasoline	Gasoline
Ignition	Electronic	Electronic	Electronic
Electric System	20 amp, regulated	20 amp, regulated	20 amp, regulated
Fuel Delivery System	Carburetor	EFI	EFI
Transmission	Hydrostatic	Hydrostatic	Hydrostatic
Drive System	2-wheel drive	2-wheel drive	Full-time 4-wheel drive
Forward Speed	8.5 mph (13.7 km/h)	8.5 mph (13.7 km/h)	8.5 mph (13.7 km/h)
Reverse Speed	6 mph (9.7 km/h)	6 mph (9.7 km/h)	6 mph (9.7 km/h)
Brakes	Internal wet disc	Internal wet disc	Internal wet disc
Steering	Power, 2-wheel steer	Power, 2-wheel steer/ Power, 2-wheel steer/ Power, 4-wheel steer	Power, 2-wheel steer
Turning Radius	25 in. (635 mm)	25 in. (635 mm)/25 in. (635 mm)/ 21 in. (533 mm)	25 in. (635 mm)
Uncut Circle Radius	28 in. (711 mm) w/ 62-in. mower	28 in. (711 mm) w/ 62-in. mower/ 28 in. (711 mm) w/ 62-in. mower/ 6 in. (152 mm) w/ 62-in. mower	28 in. (711 mm) w/ 62-in. mower
Tires	Turf	Turf/Heavy-Duty All Purpose/Turf	Heavy-Duty All Purpose
Front	18x8.50-8	18x8.50-8/18x8.50-10/18x7.00-8	18x8.50-10
Rear	26x12-12	26x12-12/26x12-12/26x10.50-12	26x12-12
Seat	15 in.	18 in./19 in./18 in.	18 in./19 in.
Lift System	Power	Power	Power
PTO	Hydraulic clutch	Hydraulic clutch	Hydraulic clutch
Dimensions:			
Height (Seat Height)	45.9 in. (1166 mm)	51.2 in. (1300 mm)/50 in. (1270 mm)/51.2 in. (1300 mm)	51.2 in. (1300 mm)/50 in. (1270 mm)
Length, Overall	75 in. (1905 mm)	75 in. (1905 mm)/78.8 in. (2002 mm) (SE)	75 in. (1905 mm)/78.8 in. (2002 mm) (SE)
Min. Storage Width (Chute Up)	57.5 in. (1460 mm) w/ 54-in. mower	65.9 in. (1674 mm) w/ 62-in. mower	65.9 in. (1674 mm) w/ 62-in. mower
Wheelbase	54.5 in. (1384 mm)	54.5 in. (1384 mm)	55.7 in. (1415 mm)
Weight, Approx.	1,101 lb. (499 kg)	1,139 lb. (516 kg)/1,199 lb. (544 kg)/1,220 lb. (553 kg)	1,263 lb. (573 kg)/1,301 lb. (590 kg)
	w/ 54-in. mower	w/ 62-in. mower	w/ 62-in. mower
Mower Options			
Cutting Width/Blades	48 in. (1219 mm) 3 blades	48 in. (1219 mm) 3 blades	48 in. (1219 mm) 3 blades
	54 in. (1372 mm) 3 blades	54 in. (1372 mm) 3 blades	54 in. (1372 mm) 3 blades
	60 in. 7-Iron (1524 mm) 3 blades	60 in. 7-Iron (1524 mm) 3 blades**	60 in. 7-Iron (1524 mm) 3 blades
	62 in. (1575 mm) 3 blades	62 in. (1575 mm) 3 blades	62 in. (1575 mm) 3 blades
Limited Warranty†	4 years / 700 hours	4 years / 700 hours	4 years / 700 hours

* The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less.

** 7-Iron mower deck not available on 4-wheel-steer models.

† X300 Series - 4yr/300 hours; X500 Series - 4yr/500 hours; X700 Series - 4yr/700 hours; whichever comes first. See the LIMITED WARRANTY FOR NEW JOHN DEERE COMMERCIAL AND CONSUMER EQUIPMENT for details.

X740/X744 (4WS)	X748 (4WD)/X748 SE
Yanmar, 3-cylinder	Yanmar, 3-cylinder
24 hp (17.9 kW)	24 hp (17.9 kW)
68.1 cu. in. (1116 cc)	68.1 cu. in. (1116 cc)
Liquid	Liquid
3	3
6.5 U.S. gal. (24.6 L)	6.5 U.S. gal. (24.6 L)
Diesel	Diesel
N/A	N/A
40 amp, regulated	40 amp, regulated
Indirect injection	Indirect injection
Hydrostatic	Hydrostatic
2-wheel drive	Full-time 4-wheel drive
8.5 mph (13.7 km/h)	8.5 mph (13.7 km/h)
6 mph (9.7 km/h)	6 mph (9.7 km/h)
Internal wet disc	Internal wet disc
Power, 2-wheel steer/ Power, 4-wheel steer	Power, 2-wheel steer
25 in. (635 mm)/21 in. (533 mm)	25 in. (635 mm)
28 in. (711 mm) w/ 62-in. mower/ 6 in. (152 mm) w/ 62-in. mower	28 in. (711 mm) w/ 62-in. mower
Turf	Heavy-Duty All Purpose
18x8.50-8/18x7.00-8	18x8.50-10
26x12-12/26x10.50-12	26x12-12
18 in.	18 in./19 in.
Power	Power
Hydraulic clutch	Hydraulic clutch
51.2 in. (1300 mm)	51.2 in. (1300 mm)/50 in. (1270 mm)
75 in. (1905 mm)	75 in. (1905 mm)/78.8 in. (2002 mm) (SE)
65.9 in. (1674 mm) w/ 62-in. mower	65.9 in. (1674 mm) w/ 62-in. mower
54.5 in. (1384 mm)	55.7 in. (1415 mm)
1,249 lb. (567 kg)/1,324 lb. (601 kg) w/ 62-in. mower	1,372 lb. (622 kg)/1,410 lb. (640 kg) w/ 62-in. mower
48 in. (1219 mm) 3 blades	48 in. (1219 mm) 3 blades
54 in. (1372 mm) 3 blades	54 in. (1372 mm) 3 blades
60 in. 7-Iron (1524 mm) 3 blades**	60 in. 7-Iron (1524 mm) 3 blades
62 in. (1575 mm) 3 blades	62 in. (1575 mm) 3 blades
4 years / 700 hours	4 years / 700 hours

X729 (4WD/4WS)	X749 (4WD/4WS)
John Deere iTorque™	Yanmar, 3-cylinder
27 hp (20.1 kW)	24 hp (17.9 kW)
45.5 cu. in. (745 cc)	68.1 cu. in. (1116 cc)
Liquid	Liquid
V-Twin	3
6.5 U.S. gal. (24.6 L)	6.5 U.S. gal. (24.6 L)
Gasoline	Diesel
Electronic	N/A
20 amp, regulated	40 amp, regulated
EFI	Indirect injection
Hydrostatic	Hydrostatic
Full-time 4-wheel drive	Full-time 4-wheel drive
8.5 mph (13.7 km/h)	8.5 mph (13.7 km/h)
6 mph (9.7 km/h)	6 mph (9.7 km/h)
Internal wet disc	Internal wet disc
Power, 4-wheel steer	Power, 4-wheel steer
21 in. (533 mm)	21 in. (533 mm)
6 in. (152 mm) w/ 62-in. deck	6 in. (152 mm) w/ 62-in. deck
Heavy-Duty All Purpose	Heavy-Duty All Purpose
18x8.50-10	18x8.50-10
26x12-12	26x12-12
18 in.	18 in.
Power	Power
Hydraulic clutch	Hydraulic clutch
51.2 in. (1300 mm)	51.2 in. (1300 mm)
75 in. (1905 mm)	75 in. (1905 mm)
65.9 in. (1674 mm) w/ 62-in. mower	65.9 in. (1674 mm) w/ 62-in. mower
55.7 in. (1415 mm)	55.7 in. (1415 mm)
1,353 lb. (614 kg) w/ 62-in. mower	1,462 lb. (663 kg) w/ 62-in. mower
48 in. (1219 mm) 3 blades	48 in. (1219 mm) 3 blades
54 in. (1372 mm) 3 blades	54 in. (1372 mm) 3 blades
62 in. (1575 mm) 3 blades	62 in. (1575 mm) 3 blades
4 years / 700 hours	4 years / 700 hours

Behind you all season long: your John Deere dealer



From the moment you enter a John Deere dealership, you can be sure you're getting the very best in customer assistance from every committed person who will be working with you. John Deere dealers are people who are in touch with your local community and who understand what it takes to maintain your land. Factory-trained service and parts professionals ensure that your equipment keeps working as hard as you do.

The best equipment deserves the best in support and service. And with a John Deere dealer, you can be assured that you will get both.

Mobile Maintenance

Service delivered, right to your front door. Our exclusive Mobile Maintenance programs bring the expertise and efficiency of our equipment experts to where you live. To get your equipment in the best shape possible, schedule your comprehensive 14-point checkup today by picking up the phone or making your appointment online at **ReadyToMow.com**.

Home Maintenance Kit

Practically everything you need to keep your John Deere tractor running smooth for years to come. Filters, plugs and oil are packaged in a convenient box.



This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specification, design and price of the products described in this literature without notice. John Deere's green and yellow color scheme, the leaping deer symbol, and JOHN DEERE are trademarks of Deere & Company.

